

**ELECTRICAL INSULATION TAPES**

PRODUCT CODE	AAS 28
DESCRIPTION	Aluminum Foil Tape
THICKNESS (mm)	Various
ADHESION (Gms/25mm)	1200
TENSILE STRENGTH (Kg/25mm)	7
BDV kV	-
TEMPERATURE RESISTANCE DEG. C	155
FEATURES / APPLICATIONS	Non-conductive adhesive. Used as a Heat shield, Grounding Static charge, EMI / RFI Shielding, etc.

For all other special Insulation requirements like: Nomex, NPN (Duplex, triplex), composite insulation, B-Stage products for coil winding, Copper coils and foils, etc. please contact our office.

YOUR PARTENERS IN THE FIELD  
 OF  
 SELF ADHESIVE PRODUCTS

ADVANCE ADHESIVE SOLUTION  
 D - 701, ORCHID ENCLAVE  
 J.B.NAGAR, ANDHERI (E)  
 MUMBAI -400 059 INDIA  
**TEL: +91 9820072458**

ADVANCE ADHESIVE SOLUTION  
 D - 23, GREATER KAILASH ENCLAVE II  
 NEW DELHI -100 048 INDIA  
 TEL: +91 9811482628

**E-MAIL: [vineet@advanceadhesive.com](mailto:vineet@advanceadhesive.com)**