

ELECTRICAL INSULATION TAPES

PRODUCT CODE	AAS 29
DESCRIPTION	Aluminum Foil Tape with Various laminations (PET, PP, PE, Paper)
THICKNESS (mm)	Various
ADHESION (Gms/25mm)	1200
TENSILE STRENGTH (Kg/25mm)	7
BDV kV	-
TEMPERATURE RESISTANCE DEG. C	155
FEATURES / APPLICATIONS	Non-conductive adhesive. Used as a Heat shield, Grounding Static charge, EMI / RFI Shielding, etc.

For all other special Insulation requirements like: Nomex, NPN (Duplex, triplex), composite insulation, B-Stage products for coil winding, Copper coils and foils, etc. please contact our office.

YOUR PARTENERS IN THE FIELD
 OF
 SELF ADHESIVE PRODUCTS

ADVANCE ADHESIVE SOLUTION
 D - 701, ORCHID ENCLAVE
 J.B.NAGAR, ANDHERI (E)
 MUMBAI -400 059 INDIA
 TEL: +91 9820072458

ADVANCE ADHESIVE SOLUTION
 D - 23, GREATER KAILASH ENCLAVE II
 NEW DELHI -100 048 INDIA
 TEL: +91 9811482628

E-MAIL: vineet@advanceadhesive.com